


[DOWNLOAD](#)


Thermal Effects on a Low Cr Modification of Ps304 Solid Lubricant Coating

By Malcolm K. Stanford

BiblioGov. Paperback. Book Condition: New. This item is printed on demand. Paperback. 28 pages. Dimensions: 9.7in. x 7.4in. x 0.1in. PS304 is a high temperature composite solid lubricant coating composed of Ni-Cr, Cr₂O₃, BaF₂-CaF₂ and Ag. The effect of reducing chromium content on the formation of voids in the Ni-Cr particles after heat treatment in PS304 coating was investigated. Coatings were prepared with Ni-20Cr or Ni-10Cr powder and in various combinations with the other constituents of PS304 (i. e. , chromia, silver and eutectic BaF₂-CaF₂ powders) and deposited on metal substrates by plasma spray. Specimens were exposed to 650 C for 24 hr or 1090 C for 15 hr and then examined for changes in thickness, coating microstructure and adhesion strength. Specimens with Ni-10Cr generally had less thickness increase than specimens with Ni-20Cr, but there was great variance in the data. Reduction of chromium concentration in Ni-Cr powder tended to reduce the appearance of voids in the Ni-Cr phase after heat exposure. The presence of BaF₂-CaF₂ resulted in a significant increase in coating adhesion strength after heat treatment, while coatings without BaF₂-CaF₂ had no significant change. Chemical composition analysis suggested that the void formation was due to oxidation of chromium in...



READ ONLINE
[7.69 MB]

Reviews

A fresh e-book with a new viewpoint. Better then never, though i am quite late in start reading this one. I am happy to explain how here is the very best ebook i actually have study during my individual lifestyle and may be he greatest pdf for actually.

-- **Diana Flatley**

This publication might be well worth a read through, and much better than other. It is amongst the most incredible book i actually have read through. I am delighted to tell you that here is the finest book i actually have read through inside my own life and could be he best ebook for possibly.

-- **Aracely Hickie**